

## FUEL SYSTEMS






### Fuel line hose (Product type 3225)

Small-diameter multi-purpose hose designed for fuel circuits (leaded and unleaded petrol, diesel).

- › Cover resists heat, oil, ozone and weathering
- › Tube has been upgraded to meet changes in fuel characteristics and resists heat and oil
- › Spiral textile reinforcement
- › Working pressure up to 1 MPa (10 kg/cm<sup>2</sup>)
- › Temperature range from -35°C to +125°C
- › Meets requirements of SAE J30R7 and DIN 73379 (except for tolerances)

Recommended for clamped hose applications on all fuel systems, including fuel injection systems.

PN					Length		Max. 
	mm	"	mm	"	m	ft	
3225-00050	3.2	7/64	8.0	1/32	15.0	49.2	1.0
3225-00051	4.0	5/32	9.7	3/8	15.0	49.2	1.0
3225-00055	5.0	13/64	10.7	27/64	15.0	49.2	1.0
3225-00052	6.0	1/4	12.2	31/64	15.0	49.2	1.0
3225-00056	7.0	9/32	13.5	17/32	15.0	49.2	1.0
3225-00053	8.0	5/16	14.2	9/16	15.0	49.2	1.0
3225-00054	10.0	3/8	17.8	45/64	10.0	32.0	1.0
3225-10014	10.0	3/8	17.8	45/64	15.0	49.2	1.0
3225-10015	12.0	15/32	19.3	49/64	15.0	49.2	1.0



Do not use for in-tank applications, sour gas, LPG and biodiesel.  
Not designed to replace coupled hose assemblies on fuel injected engines.