COOLING SYSTEMS







(Product type 4168)

This resistant and flexible radiator hose is perfect for general use on straight or slightly bent connections in heavy-duty vehicles. Approved for Marine applications.

- > Engineered to resist electrochemical degradation, the leading cause of hose failure
- > 2-ply bias fabric construction to maximise flexibility and strength
- High-performance, high-temperature resistant reinforcement
- Resists cold water leaks thanks to an advanced EPDM tube that stays soft and pliable, even under adverse operating conditions
- > Temperature range from -40°C to +135°C
- > Meets requirements of SAE 20R1, type EC, class D, standard wall

Available in 1 m lengths, cover is marked in 1 cm increments to facilitate customer-fit installation.

PN	Θ		Max. 🖸
	mm	"	MPa
4168-08019	19	3/4	0.70
4168-08022	22	7/8	0.70
4168-08025	25	1	0.70
4168-08029	29	1 1/8	0.70
4168-08032	32	1 1/4	0.70
4168-08035	35	1 3/8	0.70
4168-08038	38	1 1/2	0.70
4168-08041	41	1 5/8	0.60
4168-08044	44	1 3/4	0.53
4168-08048	48	1 7/8	0.53
4168-08051	51	2	0.42
4168-08054	54	2 1/8	0.42
4168-08057	57	2 1/4	0.42
4168-08060	60	2 3/8	0.42
4168-08064	64	2 1/2	0.42
4168-08067	67	2 5/8	0.42
4168-08070	70	2 3/4	0.46
4168-08073	73	2 7/8	0.39
4168-08076	76	3	0.18
4168-08083	83	3 1/4	0.14
4168-08089	89	3 1/2	0.13
4168-08102	102	4	0.08
4168-08114	114	4 1/2	0.08