


COUPLINGS FOR WIRE SPIRAL HYDRAULIC HOSES GLOBALSPIRAL

JIC 37° FJX

Female JIC swivel. 37° inverted cone.



								
D				A	B	H1	H2	REF.
-size	DN	"		mm	mm	mm	mm	GS
-6	10	3/8	9/16" - 18 UNF	69.0	33.2	19.1	19.1	6GS6FJX
-6	10	3/8	3/4" - 16 UNF	71.0	35.2	22.2	19.1	6GS8FJX
-8	12	1/2	3/4" - 16 UNF	72.0	34.5	22.2	22.2	8GS8FJX
-8	12	1/2	7/8" - 14 UNF	75.9	38.4	27.0	22.2	8GS10FJX
-8	12	1/2		77.0	39.5	31.8	22.2	8GS12FJX
-10	16	5/8	7/8" - 14 UNF	93.5	43.2	27.0	25.4	10GS10FJX
-10	16	5/8	1.1/16" - 12 UN	95.0	44.7	31.8	25.4	10GS12FJX
-12	20	3/4	7/8" - 14 UNF	98.4	47.4	28.6	27.0	12GS10FJX
-12	20	3/4	1.1/16" - 12 UN	98.0	47.0	31.8	28.6	12GS12FJX
-12	20	3/4	1.3/16" - 12 UN	103.2	52.2	34.9	28.6	12GS14FJX
-12	20	3/4	1.5/16" - 12 UN	102.0	51.0	38.1	28.6	12GS16FJX
-16	25	1	1.1/16" - 12 UN	107.5	50.7	34.9	34.9	16GS12FJX
-16	25	1	1.3/16" - 12 UN	107.9	51.1	38.1	34.9	16GS14FJX
-16	25	1	1.5/16" - 12 UN	109.6	53.3	38.1	38.1	16GS16FJX
-16	25	1	1.5/8" - 12 UN	115.0	58.6	50.8	38.1	16GS20FJX
-20	32	1.1/4	1.5/16" - 12 UN	129.0	57.9	41.3	44.5	20GS16FJX
-20	32	1.1/4	1.5/8" - 12 UN	136.0	64.9	50.8	47.6	20GS20FJX
-20	32	1.1/4	1.7/8" - 12 UN	137.0	65.9	60.3	47.6	20GS24FJX
-24	40	1.1/2	1.7/8" - 12 UN	124.0	50.4	60.0	55.0	24GS24FJX
-32	50	2	2.1/2" - 12 UN	148.0	56.0	75.0	65.0	32GS32FJX

-6 to -20 size are 42.0 MPa (6000 psi).

Unless otherwise stated the coupling meets the pressure rating requirements of the respective international standard.