



PLATINUM AGRO LS 80W-90

Quality class: API: GL-5
Viscosity grad: SAE: 80W-90

GENERAL FEATURES:

Mineral high quality transmission oil for all-year use in transmission of tractors, harvesters and other agricultural machinery. Recommended in particular for Limited Slip differentials.

Guarantee:

- high load bearing ability;
- excellent lubricating and anti-wear properties;
- outstanding anti-foaming performance;
- excellent thermal and oxidation stability.

APPLICATION:

Agro LS 80W-90 multigrade transmission oil is recommended for lubrication of manual transmissions of various agricultural equipment operated in severe conditions. It is recommended for use in tractors, combines and other agricultural machinery with this viscosity and quality grade specified by manufacturers.

It is recommended particularly for use in heavy-duty vehicles, agricultural equipment and other machinery with for Limited Slip differentials.

STANDARDS, APPROVALS. SPECIFICATION:

Conforms to:

MIL-L-2105D

MAN 342 M-1

Mercedes-Benz 235.0

Voith 3.325-339

Volvo 97310

Volvo 97316

Renault

ZF TE-ML 05A, 07A, 08, 16B, 16C, 16D, 16E, 17B, 19B, 21A,



RECOMMENDATIONS, REFERENCES
Farmtrac

PARAMETERS	UNIT	TYPICAL VALUES
SAE viscosity grade	-	80W-90
Kinematic viscosity at 100°C	mm ² /s	14,8
viscosity index	-	98
Flow temperature	°C	-30

NOTE:
Physicochemical parameters listed in the table are typical values. Real values are stated in quality control certificates attached to each product lot.

