



ORLEN OIL AGRO UTTO 10W-30

Quality class: API: GL-4
Viscosity grad: SAE: 10W-30

GENERAL FEATURES:

High quality multipurpose hydraulic and gear oil. Modern, unique composition of especially selected mineral bases and enriching additives allows meeting modern requirements of farming equipment manufacturers. The oils provide perfect wear and corrosion protection as well as compatibility with various sealing materials.

APPLICATION:

ORLEN OIL AGRO UTTO 10W-30 is intended for lubricating of various kind gears used in farming equipment (gear boxes, main gears, steering gears, differential gears) and it can be used in highly loaded hydraulic systems, it meets requirements of farming equipment manufacturers. Oil can be used in tractors where manual gear, axles, hydraulic fittings and "wet brakes" are lubricated by one oil system.

STANDARDS, APPROVALS. SPECIFICATION:

It meets provision of the following:

Oil is recommend to use with URSUS agricultural machines
Ford M2C 134D
Case New Holland MAT 3525, MAT 3526
John Deere JDM J20C
Massey Ferguson CMS M1143, 1135, 1145
Volvo WB101



Physical and chemical properties:

PARAMETERS	UNIT	TYPICAL VALUES
SAE viscosity grade	-	10W-30
kinematic viscosity at 100°C	mm ² /s	10.2
structural viscosity: -25°C	MPa·s	6 800
viscosity index	-	138
base value TBN	mg KOH/g	8.6
ignition temperature	°C	240
flow temperature	°C	-27
water content	% (V/V)	no content

NOTE:

Physicochemical parameters listed in the table are typical values. Real values are stated in quality control certificates attached to each product lot.

