



## PLATINUM AGRO NOVO 15W-40

**QUALITY CLASS:** API: CK-4/SN

ACEA: E9, E7

**VISCOSITY GRADE:** SAE: 15W-40

### GENERAL FEATURES:

Guarantee:

- excellent engine performance in all operating conditions;
- excellent viscosity and temperature performance;
- reduced content of sulphur, phosphor and sulphate ash (Mid SAPS) for excellent protection and longer life of diesel particulate filters and other flue gas aftertreatment solutions (EGR, SCR NOx);
- effective lubrication of friction pairs while starting cold engine and operating at low temperatures;
- effective wear control of piston and cylinder bearing surface;
- no impact on engine sealing.

### APPLICATION:

Platinum Agro NOVO 15W-40 is engine oil recommended for a broad range of agricultural machinery, including tractors, combines and other machines with this viscosity and quality grade specified by manufacturers. The oil is intended for heavy duty diesel engines operated in fields and in extreme load conditions. Suitable for use in engines meeting emission standards. It is suitable for use at any season of the year, in agricultural machinery operated on small and large farms, in municipal works and landscape maintenance. Provides excellent lubrication while starting engines in low temperatures (freezing).

### STANDARDS, APPROVALS. SPECIFICATION:

MEET REQUIREMENTS:

MAN M 3775

MAN M 3575

Deutz DQC III- 18LA

MTU Type 2.1

Caterpillar ECF-3

Detroit Diesel 93K222

Ford WSS-M2C171-F1

Allison TES 439

JASO DH-2



RECOMMENDATIONS, REFERENCES  
Farmtrac

## PHYSICAL AND CHEMICAL PROPERTIES:

Parametry	Jednostki	Wartości typowe
klasa lepkości SAE	-	15W-40
lepkość kinematyczna w temp. 100°C	mm <sup>2</sup> /s	14,8
wskaźnik lepkości	-	135
temperatura płynięcia	°C	-31
temperatura zapłonu	°C	231
liczba zasadowa TBN	mg KOH/g	8,0

Note: The above values of physical and chemical properties are typical values. Actual values are specified in quality certificates enclosed with each product lot.

