



PLATINUM AGRO STOU 10W-30

QUALITY CLASS: API: CG-4

API: GL-4

ACEA: E3

VISCOSITY GRADE: SAE: 10W-30

GENERAL FEATURES:

PLATINUM AGRO STOU 10W-30 is a high quality, multi-purpose (gear, motor, hydraulic) mineral oil. The unique and modern composition of specially selected mineral bases and additives meets the construction requirements of modern agricultural equipment manufacturers.

The oil guarantees:

- excellent lubricating and anti-wear properties,
- good compatibility with seals,
- system vibration damping,
- high resistance to oxidation,

APPLICATION:

PLATINUM AGRO STOU 10W-30 is recommended for lubrication of motors, hydraulic systems and manual transmissions in various types of agricultural machinery from different manufacturers. It is suitable for use in wet brake systems and Powershift or CVT gearboxes.

STANDARDS, APPROVALS. SPECIFICATION:

Meets the requirements of:

Massey Ferguson M1145, M1144, M1139
Ford M2C 159B, C,
John Deere JDM J27,
New Holland 82009201, 2, 3
ZF TE -ML 06A, 06B, 06C, 07B
CCMC D4, Sperry Vickers/Eaton: M2950S,
Sperry Vickers/Eaton: I-286-S,
Sauer Sunstrand/Danfoss: Hydrostatic Trans Fluid,
AFNOR NFE68603E

PHYSICAL AND CHEMICAL PROPERTIES:

Parameters	Unit	Typical values
SAE viscosity grade	-	10W-40
Kinematic viscosity at 100°C	mm ² /s	9,98
Viscosity index	-	135
FlashPour point	°C	-30
TBN base number	mg KOH/g	10,0





PLATINUM AGRO LINE

Note: The above values of physical and chemical properties are typical values. Actual values are specified in quality certificates enclosed with each product lot.

