



PLATINUM Max Expert 0W-30

OUALITY CLASS: API: SL

ACEA A5/B5

VISCOSITY GRADE: SAE: 0W-30

GENERAL FEATURES:

Synthetic, modern, all-season engine oil for the latest petrol and diesel engines. The precise formulation using the latest technology and refining additives guarantees maximum output of the power unit together with the comprehensive protection of the engine. Meets one of the latest specifications by Volvo.

Guarantees:

fuel economy,extends the life of the engine,

· maintains engine cleanliness.

APPLICATION:

PLATINUM Max Expert 0W-30 oil is designed for the application in both gasoline and diesel engines. Meeting the requirements of ACEA quality classification, it guarantees a high level of protection, even under heavy loads and in tough working conditions. It works perfectly both in the city traffic conditions and on highways. The oil is compatible with exhaust treatment devices in Volvo engines which require the Volvo approval 9520037. It can be used in other vehicles which meet Euro 6 emission standards, for which the manufacturer recommends oil viscosity class and quality specified below.

STANDARDS, APPROVALS. SPECIFICATION:

Volvo 95200377.

PHYSICAL AND CHEMICAL PROPERTIES:

Parameters	Units of measurement	Typical Values
SAE viscosity class	-	0W-30
kinematic viscosity at 100°C	mm²/s	10,3
viscosity index	-	160
pour point	⁰ C	-40
flash point	⁰ C	230
CCS at -35°C	mPa*s	6100

ORLEN OIL Sp. z o.o. ul. Opolska 114, 31-323 Kraków, tel. +48 12 665 55 00, fax +48 12 665 55 01, e-mail: <u>centrala@orlenoil.pl</u>, **infolinia:** 0 801 102 103





Total Base Number TBN Mg KOH/g 8

Note: The above values of physical and chemical properties are typical values. Actual values are specified in quality certificates enclosed with each product lot.

